

6001 Wheel Dumper

Item Number: 0620507

6001

Heavy duty design offers reliability and outstanding performance.

>> The 6001 combines a proven Perkins engine, featuring a hydrostatic transmission, with a market-leading stylish, heavy-duty design. This forward tip and power swivel bucket dumper offers massive, impact resistant box sections to ensure longevity. The 6001 is a well-balanced dumper more than capable of moving its rated payload with ease across a job site. The bucket is a critical element in the performance and longevity of any job site dumper. The bucket design of the 6001 sets a new standard for the dumper industry — offering both outstanding performance and outstanding style. <<



Additional Advantages

- Operator station is easily accessible from both sides for added convenience.
- Hydrostatic drive is easy and intuitive for the operator.
- Dashboard displays a full range of dials/indicator lights such as fuel gauge, low fuel warning light and parking brake light for operator convenience.
- Articulated steering with central hose routing allows for tight turning radius and protection of the hoses.
- Four-wheel drive provides perfect traction in difficult terrain.
- Engine cover lifts high giving excellent access to all the service points.
- Unit features standard ROPS (Roll Over Protection System) for added protection.
- Swivel bucket allows material to be unloaded on either side of the unit for ultimate versatility.

Description	Metric	Imperial
Engine Make	Perkins	
Model	Water cooled 4-cylinder diesel engine	
Operating power according to DIN-ISO 3046*	62 kW	84 hp
Fuel tank capacity	70 l	18 US gal
Speed	0 - 27 km/h	0 - 27 mph
Steering angle	+ / -33 °	+ / -33 °
Oscillation	+ / -13	
Outside turning radius	5,20 m	17.08 ft
Max. gradeability (depending on soil)	50 %	50 %
Final drive	Hydrostatic transmission, permanent 4-wheel drive, electronic driving direction switch	
Steering	Hydrostatic center-pivot	
Standard tires	405 / 70 – 20 14 Ply Traction profile	
Working brake	Foot brake via oil discs in front/rear axle	
Parking brake	Dry disc, acting on gearbox	
Length	4,83 m	14.41 ft
Width	2,26 m	7.41 ft
Max. working height	3,62 m	11.91 ft
Height over ROPS	3,10 m	10.16 ft
Height over folded ROPS	2,34 m	7.66 ft
Max. dump height	3,62 m	11.91 ft
Work pump	Gear pump	
Flow rate, work pump	55 l/min	15 US gpm
Operating pressure, work pump	220 bar	3,191 psi
Hydraulic tank capacity	70 l	18 US gal
Payload	6.000 kg	13,228 lb
Operating weight	4.320 kg	9,524 lb
Bucket capacity, struck	2,4 m ³	3.1 yd ³
Bucket capacity, heaped	3,2 m ³	4.2 yd ³
Bucket capacity, water level	1,9 m ³	2.5 yd ³

Standard Package - 6001

includes operator's manual and parts list.

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Wednesday, March 17, 2010

