

First & Only in the East.....



CRT60-74L Tier Four Final, 10ft Rider

- Hydraulic drive and electronic speed control
- Gyro assisted steering feature compensates for unwanted machine rotation
- Electro-hydraulic steering system with a choice of two steering modes
- Hydraulic wheel kit for a straightforward change of blades
- Powerful Tier 4 final engine and heavy-duty hydraulic cooling system significantly improve performance

Innovative steering system

Mode 1 Suitable for big concrete areas and for users who tend to operate the joystick with larger movements:

In **Mode 1** the signals are filtered and overmodulation of the machine prevented.



Mode 2 Suitable for tighter areas, demanding more intensive maneuvering, and for users who tend to operate the joystick with finer movements. Mode 2 enables direct and precise control.

CRT60-74L (T4F)

Dimensions



L x W x H Operating in

127 x 65 x 57

Weights

Operating weight lb

2,720

Blades and finishing data

Troweling diameter in

59

Quantity of blades

12

Blades (Float Pan Ø) in

60

Pitch range °

0 - 25

RPM -area rpm

25 - 140

Engine / Motor

Engine / Motor

Liquid-cooled, four cylinder, turbo-charged diesel

Engine / Motor manufacturer

Kohler Tier4 Final

Operating performance (SAE J1995) hp

74

RPM / speed rpm

2,600

Fuel consumption US gal/h

3.3

Tank capacity Fuel US gal

12

Runtime h

3.6